



Punctureseal

## **Punctureseal 800 ML Bottle**

### **Commercial Grade**

### **Installation Instructions**

#### **SHAKE BOTTLE WELL BEFORE USE.**

1. If you are applying to a wheel attached to a vehicle, we recommend that you jack your tyre up so that it clears the ground.
2. Position valve system at 10 o'clock or 2 o'clock and remove the valve core with the enclosed valve core remover, thereby deflating the tyre.
3. Snip off the top of the nozzle so that it will fit the tubing.
4. Secure the tubing over the open valve.
5. Squeeze the required amount of Punctureseal into the tyre using the calibrated scale on the side of the bottle.

For details on the required amount, please refer to the calculation chart online, at: <http://bit.ly/Oec88W> or for

further assistance, please visit [www.punctureseal.com](http://www.punctureseal.com) or phone +44 (0) 1428 656 554

6. Reinsert the valve core and inflate the tyre.
7. Set the tyre pressure to the correct amount recommended by the tyre manufacturer.
8. Wash away any excess product with a small amount of water.
9. Drive/ride the vehicle 15-20 miles to activate the product so as it completely coats the inner surface of the tyre. Initially it is sometimes possible to notice a slight vibration, as Punctureseal spreads its self evenly around the tyre. THIS IS NOT UNUSUAL. DRIVE THROUGH IT.

### **Punctureseal – Puncture prevention Treatment**

#### ***LIMITED WARRANTY***

Punctureseal is guaranteed to seal porosity leaks, air migration and will seal around stabbing objects up to 6mm in diameter within the TREAD AREA. It will repair the puncture for the legal life of the tyre, but if

the casing or sidewall is damaged or weakened to the point of being unsafe, limited warranty does not apply. Safety is the principle feature of Punctureseal.

#### **A SINGLE PUNCTURESEAL TREATMENT WILL:**

- Eliminate air-migration from tyres
- Provide an increase in fuel economy.
- Make tyres run cooler without changing the handling characteristics.
- Eliminate most flats and blow-outs.
- Preserve tyre casings.
- Protect wheel rims from corrosion.
- Not Ball up or dry out.

#### **Safety information incl. MSDS :**

<http://bit.ly/N1MCTn>



## Q&A

Q. Can I apply Punctureseal to a tyre already punctured?

A. Sealing capability may be reduced depending on age and condition of tyre.

Q. Do I have to prepare my tyre?

A. You need to ensure your tyre is correctly balanced before applying Punctureseal.

Q. I am not sure how to install the product, what do I do?

A. Follow our instructional videos at [www.youtube.com/puncturesealuk](http://www.youtube.com/puncturesealuk).

Q. Do I need any protective clothing?

A. No, but the product can stain delicate materials.

Q. I have found a nail in my tyre after adding Punctureseal. What do I do?

A. Remove the nail and then 'immediately' drive your vehicle for 15-20 minutes.

Q. I have found a screw in my tyre after adding Punctureseal. What do I do?

A. Remove the screw by unscrewing it (Do not pull it out) then 'immediately' drive your vehicle for 15-20 minutes.

Q. I have found a foreign object in the side wall of my tyre. What do I do?

A. Punctureseal cannot guarantee to protect you if you experience sidewall damage. Please replace the tyre.

Q. How much product do I apply in each tyre?

A. This product contains 27 x 29.5ml units of product. This, for example, is sufficient for a motorbike. A small car will require just under two bottles. To determine how much product to apply, please refer to our tyre application charts at <http://bit.ly/Oec88W> or use our online dosage calculator at <http://bit.ly/Ploxaj>.

Q. What happens if I put too much product into a tyre?

A. Up to 10% excess will not affect the performance of the product.

Q. What happens if I get product on my skin?

A. Simply wash it off with soap and water.

Q. What happens if I swallow the product?

A. Seek medical advice and drink lots of water. Refer to <http://bit.ly/N1MCTn> for information on the composition of the product. (Materials Safety Data Sheet)

Q. What happens when my tyre reaches the end of its life?

A. Replace tyre, and re-install Punctureseal.

Q. My garage tells me these products don't work?

A. Most competitor products and 'get you home' products don't work, a few may work initially until they dry out or ball up due to either low ambient temperatures or normal heat generated from the wheel and tyre. Punctureseal will not dry out or ball up and will maintain its sealing capability for the life of the tyre.

Q. I have a problem. Who do I contact?

A. Call +44 (0) 1428 656 554, email [support@punctureseal.com](mailto:support@punctureseal.com) or visit [www.punctureseal.com](http://www.punctureseal.com).

