



Punctureseal 900ml Jug

Commercial Grade

Installation Instructions

1. If not already attached, attach one end of tubing to the pump dispenser by sliding it over the opening, (hot water will help this process) and attach the other end to the quick release air chuck in the same way.
2. If not already inserted, insert the pump dispenser into the Jug and pump Punctureseal into the tubing, so that all the air with the tubing is displaced.
3. We recommend that you deflate the tyre before removing the valve core.
4. Remove Valve core and then clip the hose onto the valve stem using the quick release air chuck.
5. Pump in the required quantity of Punctureseal. Each downward compression represents 1 unit.
6. Unclip the quick release air chuck, and re-insert the valve core.

For details on the required amount, please refer to the calculation chart online, at: <http://bit.ly/Oec88W> or for further assistance, visit www.punctureseal.com or phone +44 (0) 1428 656 554

7. Re-set the tyre pressure to the correct level, as recommended by the tyre manufacturer.
8. Wash away any excess product with water.
9. Drive/ride the vehicle 15-20 minutes to activate the product, so as it completely coats the inner surface of the tyre. Initially it is sometimes possible to notice a slight vibration, as Punctureseal spreads its self evenly around the tyre. THIS IS NOT UNUSUAL. DRIVE THROUGH IT.

Punctureseal – Puncture prevention Treatment

LIMITED WARRANTY

Punctureseal is guaranteed to seal porosity leaks, air migration and will seal around stabbing objects up to 6mm in diameter within the TREAD AREA. It will repair the

puncture for the legal life of the tyre, but if the casing or sidewall is damaged or weakened to the point of being unsafe, limited warranty does not apply. Safety is the principle feature of Punctureseal.

A SINGLE PUNCTURESEAL TREATMENT WILL:

- Eliminate air-migration from tyres
- Provide an increase in fuel economy.
- Make tyres run cooler without changing the handling characteristics.
- Eliminate most flats and blow-outs.
- Preserve tyre casings.
- Protect wheel rims from corrosion.
- Not Ball up or dry out.

Safety information incl. MSDS:

<http://bit.ly/N1MCTn>



Q&A

Q. Can I apply Punctureseal to a tyre already punctured?

A. Sealing capability may be reduced depending on age and condition of tyre.

Q. Do I have to prepare my tyre?

A. You need to ensure your tyre is correctly balanced before applying Punctureseal.

Q. I am not sure how to install the product, what do I do?

A. Follow our instructional videos at www.youtube.com/puncturesealuk.

Q. Do I need any protective clothing?

A. No, but the product can stain delicate materials.

Q. I have found a nail in my tyre after adding Punctureseal. What do I do?

A. Remove the nail and then 'immediately' drive your vehicle for 15-20 minutes.

Q. I have found a screw in my tyre after adding Punctureseal. What do I do?

A. Remove the screw by unscrewing it (Do not pull it out) then 'immediately' drive your vehicle for 15-20 minutes.

Q. I have found a foreign object in the side wall of my tyre. What do I do?

A. Punctureseal cannot guarantee to protect you if you experience sidewall damage. Please replace the tyre.

Q. How much product do I apply in each tyre?

A. This product contains 84 x 29.6ml units of product. This, for example, is sufficient for 4 small cars. To determine how much product to apply, please refer to our tyre application charts at <http://bit.ly/Oec88W> or use our online dosage calculator at <http://bit.ly/Ploxaj>.

Q. What happens if I put too much product into a tyre?

A. Up to 10% excess will not affect the performance of the product.

Q. What happens if I get product on my skin?

A. Simply wash it off with soap and water.

Q. What happens if I swallow the product?

A. Seek medical advice and drink lots of water. Refer to <http://bit.ly/N1MCTn> for information

on the composition of the product. (Materials Safety Data Sheet)

Q. What happens when my tyre reaches the end of its life?

A. Replace tyre, and re-install Punctureseal.

Q. My garage tells me these products don't work?

A. Most competitor products and 'get you home' products don't work, a few may work initially until they dry out or ball up due to either low ambient temperatures or normal heat generated from the wheel and tyre. Punctureseal will not dry out or ball up and will maintain its sealing capability for the life of the tyre.

Q. I have a problem. Who do I contact?

A. Call +44 (0) 1428 656 554, email support@punctureseal.com or visit www.punctureseal.com.

